

Release: 3.3	Date: 13.04.2005
<ul style="list-style-type: none"> • Initial version for Pennview design • Eeprom patches • External Flash support 	
Release: 3.8	(Production Release) Date: 28.06.2005
<ul style="list-style-type: none"> • Country parameter 4c is set to 43 (Output Gain adjust) • Blacklisting is disabled • Speakerphone default interface is the single-ended one. • Dial monitoring on single-ended speaker enabled. 	
Release: 3.9	Date: 08.05.2006
<ul style="list-style-type: none"> • Leased-line mode is added using V.34 algorithm. • AT%T131,n added for leased-line initialization. 	
Release: 5.1	Date: 12.07.2006
<ul style="list-style-type: none"> • AT&S2 command added. If this command is issued, the DSR signal follows the state of the Hook-relay. 	
Release: 5.5	Date: 04.12.2006
<ul style="list-style-type: none"> • Fix for DTMF reception in Speakerphone mode. • Blacklisting disabled in all countries. • Eeprom defaults now integrated in the code. 	
Release: 5.5d	Date: 22.06.2007
<ul style="list-style-type: none"> • Fix for Fax class 2 implemented. • Fax ECM not supported. (too less RAM) 	
Release: 5.5e	(Production Release) Date: 08.11.2007
<ul style="list-style-type: none"> • Fix for Speakerphone mode. • S31 register for speakerphone half/full-duplex settings added. • +VNH error fixed. • DTMF reporting fixed in Speakerphone and Voice modes. 	
Release: 5.5g	(Production Release) Date: 11.06.2008
<ul style="list-style-type: none"> • Busy tone reporting in Speakerphone mode (+VLS=7) enabled. • Busy tone reporting in Voice mode (+VLS=1) enabled • AT command added to specify busy tone frequencies in the voice modes. • AT command added to disable the input/output AGC's in the voice modes. 	

DOC NR. AL4200S-S00-55G

VERSION	DATE	NAME	REMARKS	PROJECT
5.5g	18.06.08	Bircher	FW Version 5.5g	AL4200S
24.11.08			1	AL4200S-S00-55G